

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/27/2025 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form Product name : Mixture

: Tap Magic Xtra-Foamy Cutting Fluid Aerosol

1.2. Recommended use and restrictions on use

Recommended use Restrictions on use : Cutting fluids: No data available

1.3. Supplier

The Steco Corporation 2330 Cantrell Road Little Rock, AR 72202 USA T 800-643-8026 <u>steco@tapmagic.com</u>

1.4. Emergency telephone number

Emergency number

: 800-255-3924

2.1. Classification of the substance o	r mixturo
GHS US classification	
Flammable aerosol Category 1	H222;H229 Extremely flammable aerosol. Pressurized container: may burst if heated
Full text of H statements : see section 16	
2.2. GHS Label elements, including p	recautionary statements
GHS US labeling	
Hazard pictograms (GHS US)	
Hazard pictograms (GHS US) Signal word (GHS US)	: Danger
	: Danger : H222 - Extremely flammable aerosol
Signal word (GHS US)	
Signal word (GHS US) Hazard statements (GHS US)	 H222 - Extremely flammable aerosol H229 - Pressurized container: may burst if heated P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Signal word (GHS US)	 H222 - Extremely flammable aerosol H229 - Pressurized container: may burst if heated P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Signal word (GHS US) Hazard statements (GHS US)	 H222 - Extremely flammable aerosol H229 - Pressurized container: may burst if heated P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Other hazards which do not result in classification : Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown acute toxicity (GHS US)

No additional information available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)
Distillates (petroleum), hydrotreated light naphthenic	CAS-No.: 64742-53-6	7-13
Propane	CAS-No.: 74-98-6	3-7
Butane	CAS-No.: 106-97-8	3-7

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general First-aid measures after inhalation	 If you feel unwell, seek medical advice (show the label where possible). Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor. If breathing stops, give artificial respiration. 	
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.	
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell. Rinse mouth out with water.	
4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after inhalation	: At high concentrations, the vapors can be irritating to the respiratory system.	
Symptoms/effects after skin contact	: No known significant effects or critical hazards.	
Symptoms/effects after eye contact	: May cause eye irritation.	
Symptoms/effects after ingestion	: Possible irritation of mucous membranes and digestive tract, nausea, vomiting.	

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard	:	Extremely flammable aerosol.
Explosion hazard	:	Contains gas under pressure; may explode if heated.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released. Combustion products may include the following: carbon oxides (CO, CO2).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental releas	e measures
6.1. Personal precautions, protec	tive equipment and emergency procedures
General measures	No action shall be taken without appropriate training or involving any personal risk. Ventilate spillage area. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Prevent runoff from entering drains, sewers or waterways. Remove all sources of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
6.1.1. For non-emergency personnel	
Protective equipment Emergency procedures	 Wear recommended personal protective equipment. Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, spray, vapors, gas. No open flames, no sparks, and no smoking.
6.1.2. For emergency responders	

: Do not attempt to take action without suitable protective equipment. For further information refer

Protective equipment

Emergency procedures

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or
	streams. Collect spillage. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Collect all waste in suitable and labeled containers
	and dispose according to local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

to section 8: "Exposure controls/personal protection". : Evacuate unnecessary personnel. Stop leak if safe to do so.

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Precautions for safe handling	Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Keep away from sources of ignition - No smoking. Avoid breathing gas, mist, spray, vapors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Hygiene measures	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product Always wash hands after handling the product. Handle in accordance with good industrial hygiene and safety procedures. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
--------------------	---

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions

: Store in a well-ventilated place. Keep away from food, drink and animal feeding stuffs. Keep container closed when not in use. Keep away from heat. Keep away from ignition sources (including static discharges). Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tap Magic Xtra-Foamy Cutting Fluid Aerosol		
No additional information available		
Propane (74-98-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Propane	
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant	
Regulatory reference	ACGIH 2024	
USA - OSHA - Occupational Exposure Lin	nits	
Local name	Propane	
OSHA PEL TWA	1800 mg/m³	
	1000 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Butane (106-97-8)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Butane	
ACGIH OEL STEL	1000 ppm (EX - Explosion hazard)	
Remark (ACGIH)	TLV® Basis: CNS impair	
Regulatory reference	ACGIH 2024	
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)		
USA - OSHA - Occupational Exposure Limits		
Local name	Oil mist, mineral	
OSHA PEL TWA	5 mg/m³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

8.2. Appropriate engineering controls

Appropriate engineering controls

Environmental exposure controls

- Ensure good ventilation of the work station.Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol can. Amber liquid.
Color	: Amber
Odor	: Characteristic
Odor threshold	: No data available
рН	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: >150°C (302°F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.3
Solubility	: Not soluble in water alone.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: >370°C (698°F)
Decomposition temperature	: No data available
Viscosity, kinematic	: 1100 mm²/s (40°C (104°F))
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content

: 0.27 lbs/gal

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from ignition sources. Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong bases. Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Propane (74-98-6)		
LC50 Inhalation - Rat [ppm]	800000 ppm	
Butane (106-97-8)		
LC50 Inhalation - Rat [ppm]	> 800000 ppm	
Distillates (petroleum), hydrotreated li	ght naphthenic (64742-53-6)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	2.18 mg/l	
Skin corrosion/irritation	Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
Viscosity, kinematic	: 24 mm²/s (40°C (104°F))	
Likely routes of exposure	: Inhalation. Skin and eye contact.	
Symptoms/effects after inhalation	: At high concentrations, the vapors can be irritating to the respiratory system.	
Symptoms/effects after skin contact	: No known significant effects or critical hazards.	
Symptoms/effects after eye contact	: May cause eye irritation.	
Symptoms/effects after ingestion	: Possible irritation of mucous membranes and digestive tract, nausea, vomiting.	

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Propane (74-98-6)		
LC50 - Fish [1]	> 100 mg/l	
Butane (106-97-8)		
LC50 - Fish [1]	27.98 mg/l	
EC50 96h - Algae [1]	16.47 mg/l	
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)		
LC50 - Fish [1]	> 5000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l	
EC50 96h - Algae [1]	> 1000 mg/l	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations		
13.1. Disposal methods		
Regional waste regulation	: Disposal must be done according to official regulations.	
Waste treatment methods	 Dispose of contents/container in accordance with licensed collector's sorting instructions and in accordance to local and regional legislation. Dispose of contents/container in accordance with licensed collector's sorting instructions. 	
Sewage disposal recommendations	: Do not discharge into drains. Disposal must be done according to official regulations.	
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.	

: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	ΙΑΤΑ
14.1. UN number			
1950	1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable

Additional information

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	ΙΑΤΑ		
14.3. Transport hazard class(es	14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1		
PLANAALE GAS					
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No		
No supplementary information available	ble	l	I		

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Propane	74-98-6	Present	Active	
Butane	106-97-8	Present	Active	
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	Present	Active	

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Canada

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Butane (106-97-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

Component	State or local regulations
Propane(74-98-6)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Butane(106-97-8)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Distillates (petroleum), hydrotreated light naphthenic(64742-53-6)	U.S Massachusetts - Right To Know List

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H222	Extremely flammable aerosol

Abbreviations and acronyms		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms		
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

NFPA health hazard	: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard	: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating	
Health	: 0 Minimal Hazard - No significant risk to health
Flammability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

BW_Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.